

[Home](#) >> [Small/Medium Business](#) >> [Products](#) >> [Surge Protection and Power Conditioning](#) >> [Surge Protection Devices](#) >> [Product Family](#)



## APC Performance SurgeArrest 11 Outlet with Phone (Splitter), Coax and Ethernet Protection, 120V


**Part Number:** P11VNT3



### Output

|                   |            |
|-------------------|------------|
| Number of Outlets | 11         |
| Receptacle Style  | NEMA 5-15R |

### Input

|                        |  |
|------------------------|--|
| Nominal Input Voltage  | 120V   |
| Input Frequency        | 50/60 Hz   |
| Input Connections      | NEMA 5-15P  |
| Cord Length            | 8 feet (2.44 meters)   |
| Input Breaker Capacity | 15A  |

### Surge Protection and Filtering

|   |   |
|---|---|
| Surge energy rating                         | 2030 Joules   |
| eP Joule Rating                             | 3400  |
| EMI/RFI Noise rejection (100 kHz to 10 MHz) | 70 dB   |
| Data Line Protection                        | RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines),RJ45 10/100 Base-T Ethernet protection,Cable modem / Video protection |
| Let Through Voltage Rating                  | < 40  |

### Physical

|                |                      |
|----------------|----------------------|
| Net Weight     | 2.33 lbs. (1.06 kg)  |
| Maximum Height | 1.57 inches (40 mm)  |
| Maximum Width  | 4.70 inches (119 mm) |
| Maximum Depth  |                      |

**Environmental**

|                             |                               |
|-----------------------------|-------------------------------|
| Operating Environment       | 32 - 113 °F (0 - 45 °C)       |
| Operating Relative Humidity | 0 - 95%                       |
| Operating Elevation         | 0-10000 feet (0-3000 meters)  |
| Storage Temperature         | 5 - 113 °F (-15 - 45 °C)      |
| Storage Relative Humidity   | 0 - 95%                       |
| Storage Elevation           | 0-50000 feet (0-15000 meters) |

**Conformance**

|                             |                         |
|-----------------------------|-------------------------|
| Regulatory Approvals        | CSA,NOM,UL 1363,UL 1449 |
| Standard Warranty           | Lifetime                |
| Equipment protection policy | Lifetime : \$100000     |
| UL 1449 TVSS Rating         | 330V                    |

\*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved