

[Home](#) >> [Small/Medium Business](#) >> [Products](#) >> [Surge Protection and Power Conditioning](#) >> [Surge Protection Devices](#) >> [Product Family](#)



APC Performance SurgeArrest 11 Outlet with Phone (Splitter) and Coax Protection, 120V

Part Number: P11VT3



Output

| | |
|-------------------|------------|
| Number of Outlets | 11 |
| Receptacle Style | NEMA 5-15R |

Input

| | |
|------------------------|----------------------|
| Nominal Input Voltage | 120V |
| Input Frequency | 50/60 Hz |
| Input Connections | NEMA 5-15P |
| Cord Length | 8 feet (2.44 meters) |
| Input Breaker Capacity | 15A |



Surge Protection and Filtering

| | |
|---|---|
| Surge energy rating | 3400 Joules |
| EMI/RFI Noise rejection (100 kHz to 10 MHz) | 70 dB |
| NM Surge Response Time (ns) | 1 ns |
| Data Line Protection | RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines), Cable modem / Video protection |
| Data Lines Protected (multi-line only) | 1-4 |
| Let Through Voltage Rating | < 40 |

Physical

| | |
|----------------|---------------------|
| Net Weight | 2.33 lbs. (1.06 kg) |
| Maximum Height | 1.57 inches (40 mm) |
| Maximum Width | |

Environmental

| | |
|-----------------------------|-------------------------------|
| Operating Environment | 5 - 113 °F (-15 - 45 °C) |
| Operating Relative Humidity | 0 - 95% |
| Operating Elevation | 0-10000 feet (0-3000 meters) |
| Storage Temperature | 5 - 113 °F (-15 - 45 °C) |
| Storage Relative Humidity | 0 - 95% |
| Storage Elevation | 0-50000 feet (0-15000 meters) |

Conformance

| | |
|-----------------------------|---------------------|
| Regulatory Approvals | CSA,UL 1363,UL 1449 |
| Standard Warranty | Lifetime |
| Equipment protection policy | Lifetime : \$100000 |
| UL 1449 TVSS Rating | 330V |

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved